

QUOTATION NO 507HP24S-2024

This quotation list all of the equipment required by the U.S. Department of Transportation and Transport Canada to properly re qualify cylinders used to transport hazardous materials (pressurized gas).

This equipment will allow you to re qualify cylinders to 34" tall. Options are listed at the end of the quotation that will offer faster, easier and more accurate cylinder testing.

Please see last page for important Training-Licensing and Leasing Information

Part No.	Description	Price
507-HP-24S-M	<p>Hydrostatic Water Jacket Cylinder Test Station</p> <ul style="list-style-type: none"> • Test Range of 2000 – 10,000 psi in Automated Mode • Test Range of 2000 – 10,000 psi in Manual Mode • Meets U.S. D.O.T. Requirements <p><u>Includes:</u></p> <p>⇒ Air Operated Pressure Test Pump</p> <ul style="list-style-type: none"> ✓ Stainless Steel Water Section ✓ Soft Seated Check Valves ✓ Contaminant Free Design (for testing of O₂ cylinders) <p>⇒ 24" Dia x 40" Tall Water Jacket (Test Chamber)</p> <ul style="list-style-type: none"> ✓ Accepts Cyls. Up To 22"Dia x 34"Tall ✓ High & Low-Pressure Air Bleed Valves ✓ Quick Acting Manual Cam Clamps Lid Closure ✓ Floor Mounted Drain Pan – <i>No Pit Required</i> <p>⇒ Calibrated Master Pressure Gauge (used for periodic verification)</p> <ul style="list-style-type: none"> ✓ 11,000 psi x 20 psi Increments – 8.5" Diameter ✓ Class 3A, 1/4% Accuracy <p>⇒ Calibrated Cylinder for Full Test Range</p> <p>⇒ Digital Expansion Scale</p> <ul style="list-style-type: none"> ✓ 0-700cc Net Expansion x 0.1cc Increments <p>⇒ Automated Features</p> <ul style="list-style-type: none"> ✓ Software Driven Test Records ✓ Ability to Set Up Template Cylinder Information ✓ Calculates Pass / Fail Automatically Based on Cyls. Parameters ✓ All Test Results and Math Calculated Automatically ✓ Allows for "+" Testing REE Entry ✓ Test History Screen Allows for Export and Sorting of Fields ✓ Automated Calibrated Cylinder Testing with Results ✓ Optional Warning of Improper Calibrated Cylinder Verification <p><u>Hardware</u></p> <ul style="list-style-type: none"> ✓ Laptop - printer <p>⇒ Training Seminar at our Facility</p> <ul style="list-style-type: none"> ✓ Receive D.O.T. required training for up to 4 of your employees ✓ Valid for up to 90 days after purchase of test system <p>⇒ Ability to Operate Manually for Ease in Troubleshooting</p> <p>⇒ Enamel Painted Steel Cabinet</p> <p>⇒ Set of 7 Test Adapters</p> <p>⇒ Written Instructional Manual</p> <p>⇒ Calibration Certificates</p>	\$ 23,700.00
510-010	<p>Pneumatic Operated Vise Station</p> <ul style="list-style-type: none"> ✓ Air Operated (60 psi) ✓ Rubber Belted to Protect Cyls. ✓ Accepts Cyls. to 12" Diameter ✓ Adjustable / Removable Shelf Plate ✓ 24" Square Steel Base Plate 	2,100.00
530-020	Cylinder Hot Air Dryer - Designed for Cylinders Under 36" Tall	2,200.00



Hydro-Test Products Inc.
 85 Hudson Road Stow, Massachusetts 01775 USA
 Tel: 800-225-9488 / 978-897-4647 Fax: 978-897-1942
www.hydro-test.com

	<ul style="list-style-type: none"> ✓ Heavy Duty Design ✓ 115VAC Electrical ✓ Six Cylinder Capacity ✓ Stainless Steel Heating Element 	
540-003	Inversion Rack <ul style="list-style-type: none"> ✓ Designed for Inversion of Portable Size Cyls. to Expel Test Water ✓ Adjustable for Cylinders 24" to 32" Tall ✓ Adjustable Safety Strap ✓ Steel Construction 	740.00
230-206	Internal Cylinder Cleaning Whip <ul style="list-style-type: none"> ✓ Removes loose rust and oxide coating ✓ Designed for cyls up to 36" Tall ✓ Fits onto 3/8" drill ✓ Stainless steel wire 	89.00
230-033	1000 lb. Capacity Electric Hoist <ul style="list-style-type: none"> ✓ 115VAC – ½ HP ✓ 16 ft. / minute Lift Speed ✓ Push Button Control 	4,100.00
230-037	Chain Bucket for Hoist	145.00
230-040	Trolley for Hoist	350.00
240-140	Adjustable Valve Removal Wrench <ul style="list-style-type: none"> ✓ Fits Valves with 2 Flat Sides ✓ Designed for Industrial Gas Valves ✓ Manufactured of Hardened Machined Steel 	135.00
240-143	Wrench for Medical Post Valves <ul style="list-style-type: none"> ✓ Replaceable Durable Delrin Insert – Protects Valve Finish ✓ ½" Opening for Torque Wrench ✓ Fast and Easy Fitting 	240.00
240-145	Wrench for SCBA Air Pak Valves <ul style="list-style-type: none"> ✓ Machined to Fit Snug Over Valve ✓ 3/4" Male Hex on Top - Allows Use of 3/4" Socket ✓ Fast and Easy to Use ✓ Use With Torque Wrench to Tighten To Manufacturers Specs. 	90.00
230-064	5/16" Characters, 0-9 Stamp Set (1/2" shank) <ul style="list-style-type: none"> ✓ Best Grade for Marking of Steel and Aluminum Cylinders 	89.00
230-063	1/4", Characters, 0-9 Stamp Set (Low Stress) (1/2" shank) <ul style="list-style-type: none"> ✓ For Marking of Specification 3HT Cylinders 	89.00
230-136	Pneumatic Stamping Gun <ul style="list-style-type: none"> ✓ Accepts ½" Shank Size Stamps ✓ Air Operated on 40 psi ✓ Saves the Life of Your Stamps ✓ Easy – Fast and Safe ✓ Operates Similar to an Air Chisel 	269.00
69-099	Internal Cylinder Inspection Light (white light & ultraviolet) <ul style="list-style-type: none"> ✓ Long life LED for complete illumination of cyls. ✓ 13.5" Length of wand ✓ Warm white LEDs best simulate incandescent light ✓ Ultra-violet light source meets CGA G-4.1 for O₂ cyl. inspection ✓ Low voltage for use in hazardous locations 	335.00
69-102	Internal Cylinder Inspection Light <ul style="list-style-type: none"> ✓ Fiber Optic Design ✓ High Intensity ✓ 150 Watt Bulb ✓ 115V – 50/60 Hz 	725.00
69-110	Probe for Fibre Optic Inspection Light <ul style="list-style-type: none"> ✓ 5' Long 	125.00



69-058	Inspection Mirror for Cylinder Threads (3/8" diameter)	21.00
69-075	Optical Plus Thread Magnifier (for cylinder thread inspection) <ul style="list-style-type: none"> ✓ Battery Operated ✓ Rugged, anodized, aluminum construction. ✓ Adjustable focusing for clearer and brighter viewing. ✓ Adjustable light intensity for differing surface reflectivity. ✓ 4X magnification for the closest thread view possible. ✓ Single unit capable of inspecting: SCUBA, Medical, SCBA, AFV, Industrial Specialty Gas and CO2. 	625.00
69-050	Combination Dial Caliper & Pit Gauge <ul style="list-style-type: none"> ✓ 2 tools in one ✓ Allows measuring of pits/gouges as required by CGA C-6 pamphlet ✓ Allows measuring of valves and test adapters ✓ Steel construction ✓ Easy to read dial gauge 	54.00
240-150	Breaker Bar Tool designed for inserting and removing tapered thread test adapters and socket type valves safely – easily and efficiently <ul style="list-style-type: none"> ✓ 18" Total length ✓ ½" drive head swivels 180° ✓ 376 ft-lbs maximum torque ✓ 3-way ratcheting action: Right or Left handed thread, or lock 	49.00
240-160	1 ½" Impact Socket x ½" Drive For use with #240-150 Breaker Bar	52.00
393-001	Test Record Forms (50 sheets/pad)	13.50
393-018	Test Label for Composite Wrapped SCBA Cylinders (50 labels / Roll)	15.00
393-020	Epoxy Kit for SCBA Test Labels	24.50
507-RBLD	Spare Parts Kit of Typical Consumable Items (O-rings, seals, valves, couplers ...)	925.00
393-290	C.G.A. Pamphlets <ul style="list-style-type: none"> ✓ Set of 7 ✓ C-1, C-5, C-6, C-6.1, C-6.2, C-6.3, C-8 ✓ Required if Licensed by US D.O.T. or Transport Canada 	775.00
393-185	DOT Title 49 Parts 100-185 Code of Federal Regulations Book <ul style="list-style-type: none"> ✓ Required if licensed by US D.O.T. 	59.00

Subtotal: \$38,134.00

Utilities Required to Operate Equipment: ([click here for floor plan](#))

- Stable and consistent air and water temperatures
- Inlet water supply
- Overhead I-Beam for hoist and trolley
- 8CFM of 100 psi pre regulated shop air (3 drops)
- 10' Ceiling height
- 115V-20amp electrical (4 drops)

OPTIONS:		Add:
500-201	Pneumatic Lid Closures on Water Jacket in Place of Manual Closures <ul style="list-style-type: none"> ✓ Fast – easy to operate air powered clamps ✓ On / off control valve panel - Operates on 100 psi of shop air ✓ Generates a more positive seal than manual clamps 	\$ 5,000.00



Hydro-Test Products Inc.
 85 Hudson Road Stow, Massachusetts 01775 USA
 Tel: 800-225-9488 / 978-897-4647 Fax: 978-897-1942
www.hydro-test.com

500-225	<p>Multi Cylinder Lid Assembly A Tremendous Time Saver and Productivity Enhancer. Is a Great Way to Enhance Your Hydro-Test Profitability. Designed for Those Companies Testing A Quantity Of Similar Size Cylinders.</p> <p>Features:</p> <ul style="list-style-type: none"> ✓ 14" Lid with three outside spuds to accept 3 cylinders to 10.0" dia. ✓ Also has one open middle spud for testing 1 cylinder to 16" diameter ✓ Cylinders are tested individually ✓ Allows loading / un-loading of 3 cylinders at one time ✓ Eliminates 2/3rds of time-consuming loading / un-loading procedure ✓ Includes quick disconnect couplers & high/low-pressure bleed valves ✓ For use with Hydro-Test Products brand 24" diameter water jacket 	<p>\$ 3,300.00</p>
393-450	<p>On Site Assistance with Set up and Training</p> <p><u>Includes;</u></p> <ul style="list-style-type: none"> ✓ Hydro-Test technician onsite for 1 day at your location ✓ Verification of proper setup of equipment ✓ Operational training on running daily verification ✓ Operational training on testing cylinders ✓ Trouble shooting of potential problems ✓ Review of proper record keeping ✓ DOT Hazmat training if required <p><i>Prior to Hydro-Tests technician arrival the following must be prepared;</i></p> <ul style="list-style-type: none"> ✓ Utilities as described in quotation in place and operational ✓ Two hookups from test console to water jacket in place ✓ Water jacket in pit (if required) ✓ Water jacket and calibrated cylinder filled with water 48 hours prior to technician's arrival. ✓ Please allow a minimum of 45-day notice to schedule on-site training 	<p>Typically \$3,500 - \$6,000 depending upon location in the USA</p> <p>Foreign locations will be at a significantly higher cost</p> <p>Contact us for pricing based on training location</p>

Terms: **Discount is available** with prepayment terms (please [contact](#) our sales office for details)

F.O.B: [Stow, Massachusetts, USA](#), all freight cost are the responsibility of the purchaser.
We will be pleased to offer delivered pricing upon request.

Delivery: Typically ship in 6 weeks

Valid: Prices are subject to change without notice

Warranty: All Hydro-Test Products manufactured equipment is warranted for a period of 12 months under normal usage, commencing after receipt of order. For items not manufactured by Hydro-Test Products the original manufacturer's warranty shall be in effect. Consumable items such as O-rings, Seals, Valves, etc... are warranted for 30 days under normal usage. All warrantee work is provided F.O.B. Stow, Massachusetts, USA.

Packaging: Best commercial packaging is included in the pricing. If export crating or other specialized or unique packaging is required an additional charge may apply.

Thank you for the opportunity to offer this quotation. To see pictures on the above products, please click on the **part no's** and you will be redirected to those items.

You can download our complete [catalog at this link](#)

Best regards,

Jon Gorman



Hydro-Test Products Inc.
85 Hudson Road Stow, Massachusetts 01775 USA
Tel: 800-225-9488 / 978-897-4647 Fax: 978-897-1942
www.hydro-test.com

[Jon Gorman](#)

Hydro-Test Products Inc.

Important Informational Links:

- 1) Please [click here for a list of Independent Inspection Agencies](#) (IIA) for the U.S. Department of Transportation. To requalify cylinders in the USA, or operate outside of the USA and be DOT certified, an inspection of your facility is required after equipment is installed & operational and training has been completed.
- 2) Please [click here for information regarding the training and licensing requirements](#) for Transport Canada (TC). To requalify cylinders in Canada, or operate outside of Canada and be TC certified, an inspection of your facility is required after equipment is installed & operational and training has been completed.
- 3) [Browse all of our training opportunities](#). We offer operational and DOT required hazmat for cylinder re-qualifiers in various ways. Here is a [Training Development Guide](#) to help determine the best training option for your company and employees.
- 4) Leasing of our equipment is available through www.dicapcredit.com. Use this [Leasing Calculator](#) to calculate what your monthly cost will be when leasing through Diversified Capital Credit. *Due to special arrangements made between Hydro-Test and DC, when you lease through them, you will receive a prepayment discount.*

Frequently Asked Questions:

(Q) Is the equipment difficult to operate?

(A) The test system has been designed for easy operation. Test procedure can be mastered in ½ day

(Q) Do I need to travel to Hydro-Test's facility in Massachusetts to receive training?

(A) As an option we have provided an estimated quotation for on-site training at your facility. Hydro-Test has technicians that travel extensively around the world installing and providing training on our equipment. The training provided at Hydro-Test in Stow, Massachusetts is included in the price of the test system. Training at your facility is shown as an option and includes travel – hotel and onsite cost.

(Q) Can I Upgrade My Test Station in 5 Years?

(A) Yes, and it is a very good reason to purchase your cylinder testing equipment from Hydro-Test. We understand that what you are testing today may not be what you want to test in 5 years. Hydro-Test offers larger test jackets – ability to switch from burette tubes to digital readouts – replace manual lid closures with pneumatics ... without reinvesting \$1000's of dollars in duplicate equipment.

(Q) How Many Cylinders Can I Test in 1 Day?

(A) This is a difficult question to answer as much depends on the operator, type(s) of cylinders, number of operators and more. Typically 1 operator testing portable size cylinders (i.e. 20Lb CO2, SCUBA, SCBA) should be able to test 6 – 8 cylinders per hour (48-64 per day) on a manual operated system. Typically an automated test system will increase the output by 25%

(Q) Are there any additional cost involved?



Hydro-Test Products Inc.
 85 Hudson Road Stow, Massachusetts 01775 USA
 Tel: 800-225-9488 / 978-897-4647 Fax: 978-897-1942
www.hydro-test.com

(A) Initially, in the USA, there is a fee for the DOT inspection. Pressure gauge recalibration is required every 6 months (~\$170.00 / year). Consumable test system parts, o-rings, seals, valves ..., are typically \$100.00 - \$300.00 per year depending on your testing volume.



Hydro-Test Products Inc.
85 Hudson Road Stow, Massachusetts 01775 USA
Tel: 800-225-9488 / 978-897-4647 Fax: 978-897-1942
www.hydro-test.com